

CONDITIONS FOR ACCEPTANCE

Asbestos waste, brittle or unbound

EURAL code	170601*
Waste code	042002

DESCRIPTION

Brittle or unbound asbestos waste, such as plaster insulation, sprayed asbestos, soft asbestos plates, rope seal, asbestos felt or cardboard and badly weathered asbestos cement

ADDITIONAL CONDITIONS

General conditions:

- No radioactive material
- No large pieces of metal or large non-shreddable objects

Packaging conditions:

- The asbestos waste must be packed airtight and double-walled in strong UN approved bags or big bags marked with ADR label (class 9) and asbestos logo with the following text: "a, asbestos, caution contains asbestos, inhaling asbestos dust is damaging to health, observe the safety instructions".
- If the asbestos waste is delivered in bags, these must be double-walled, sufficiently strong and tear resistant, bearing the asbestos logo. Woven bags are not permitted. The maximum weight is 25 kg. The maximum dimensions of the bags are 1100 mm x 630 mm.
- If the asbestos waste is delivered in big bags, these must meet the following criteria:
 - Dimensions max. 90 x 90 x 125 cm
 - Safety closure at the top
 - Flat bottom underneath
 - Completely double-walled (PP coated cloth)
 - Airtight seal
 - Bearing the asbestos logo
 - UN approved
 - Max. weight: 1000 kg
 - Fitted with 4 loops for loading with forklift truck
- Larger objects such as pipes, ovens and doors may, subject to prior written consent, be delivered in alternative packaging that meets the following criteria as a minimum:
 - Airtight and double-walled packaging
 - Bearing the asbestos logo
 - On a pallet or with 4 loops for loading with forklift truck
 - Anchoring of packaged large objects on their palettes
- Asbestos waste that does not meet the aforementioned packaging requirements will have to be repacked. Extra charges will be levied for this.