

CONDITIONS FOR ACCEPTANCE

Blasting grit, for solidification

EURAL code	120116*
Waste code	128003

DESCRIPTION

Blasting grit and blasting dust, contaminated with rust, paint and other coatings, loose in 200 l metal drum, ASP or plastic box with lid.

ADDITIONAL CONDITIONS

Parameters:

- Flashpoint: > 61°C
- Mineral oil: max 5%/kg DS
- Solvent: max. 3%/kg DS
- Loss of incandescence: max 10%
- Extractable organohalogens: max. 1000 mg/kg DS
- Free cyanides: max. 250 mg/kg DS

General conditions:

- The MSDS of the used blasting grit will be sent to Renewi beforehand
- The blasting grit/blasting dust must not contain any pyrophoric metal powders such as Al, Mg or Zn
- Contamination with heavy metals (Cr, Ni, etc.) must be limited
- The blasting grit/blasting dust must not be contaminated with other waste
- The blasting grit/blasting dust must not contain foreign objects
- The blasting grit/blasting dust must not contain big metal objects
- For large amounts (> 3 tonnes per collection) analysis will be requested beforehand

Packaging conditions:

- The blasting grit/blasting must not be packed in small bags but must be left loose in the boxes.
- Max. weight per plastic box: 450 kg
- Max. weight per ASP: 1000 kg