

CONDITIONS FOR ACCEPTANCE

Waste containing asbestos or suspect asbestos-containing materials

DESCRIPTION

Asbestos or suspect asbestos-containing materials from selective demolition or dismantling

Permitted

- Selectively removed asbestos with <10 v% organic matter
- Materials containing asbestos such as roofing sheets, brake blocks, brake discs, gaskets and insulation material
- Presumed or suspect asbestos-containing materials
- Eternit roofing sheets
- Safes

Prohibited

- Hazardous waste
- Construction and demolition waste
- Commercial waste
- Steel containing asbestos

Packaging requirements

Asbestos or waste containing asbestos must be delivered in sealed, double packaging of sufficient strength (minimum thickness of single packaging 0.2 mm) or in a big bag, container bag or depot bag with an inner liner. The packaging must be marked 'waste containing asbestos'. Sharp objects or edges must be shielded in such a way that the container depot bag cannot be damaged. The container bag may not be larger than 17 m³ (maximum 10 tonnes, unless stated otherwise) and must be properly sealed upon delivery.

Exceptions from these packaging requirements may occur and must be discussed in advance. Exceptions are:

- Bulky objects: if the size of the waste is such that it does not fit in an asbestos bag (long sheets, fire safes)
- Asbestos cement pipes, drinking water pipes or similar materials with a diameter in excess of 100 mm. These pipes must be delivered double-wrapped in plastic of at least 0.5 mm thickness.

** If, upon delivery, deviations are found from the described conditions, Renewi Nederland B.V. reserves the right to refuse the consignment in question or to accept it according to amended conditions.*

*** Your obligation and opportunity to separate can be found in the National Waste Management Plan (LAP)*