CONDITIONS FOR ACCEPTANCE



Waste wood – chipboard for recycling

DESCRIPTION

Wood quality chipboard that is broken and after purification used in the production of new chipboard.

Permitted

- Standard chipboard
- Moisture-proof chipboard
- Fire-retardant chipboard
- Melamine-faced chipboard
- Chipboard containing edge banding (veneer) < 5%

Prohibited

- Chipboard with HPL
- Chipboard with edge banding (veneer) > 5%
- Chipboard with Flameshield
- OSB, MDF, plywood, Triplex, Multiplex
- Grade A, B and C wood (B-wood: other than as permitted)
- High pressure laminate, Trespa
- Mineral bonded wood wool board (fibreboard with cement mortar)
- Dolphin or mooring wood
- Burnt wood
- Garden and green waste
- Rotting or mouldy wood
- Wood dust, sawdust
- Hinges and locks, nails, screws or bolts larger than 10 mm in diameter as well as S hooks
- Hazardous waste
- Construction and demolition waste
- Commercial waste
- Other waste materials such as textiles, sand, rubble, soil, roofing, paper, metals, corrugated iron, ceiling tiles, plastics, glass, insulation material, etc.

^{*} If, upon delivery, deviations are found from the described conditions, Renewi Nederland B.V. reserves the right to refuse the consignment in question or to accept it according to amended conditions.

^{**} Your obligation and opportunity to separate can be found in the National Waste Management Plan (LAP)